

ISBN 978-4-9902356-7-3



Department of Earth Resources Engineering
Kyushu University
Fukuoka, Japan

The Institute of Economics and Control Systems
Faculty of Mining and Geology, VSB – Technical University of Ostrava
Ostrava, Czech Republic



Faculty of Earth Sciences and Material Technology, ITB
Bandung, Indonesia

Mining and Materials Processing Institute, Japan (MMIJ)

Proceedings of
***4th International Workshop on
Earth Science and Technology***

Sponsored by
Faculty of Engineering, Kyushu University,
Kyushu University Foundation,
MMIJ-Kyushu Branch,
And MMIJ-Division of Coal Mining Technology

FUKUOKA DECEMBER 2006

© by Kyushu University 2006

CONTENTS

ROLE OF ROCK MASS CHARACTERISTIC AND ROCK TOUGHNESS ON PREDICTING CUTTING PERFORMANCE OF RAISE BORING MACHINE

Suseno KRAMADIBRATA and B.DWINAGARA

1

ZETA-POTENTIAL MEASUREMENT AND SONOCHEMICAL TREATMENT OF HINAI GREEN TUFF COLLOID FOR REUSE

Hirokazu OKAWA, Takashi NAKAMURA and Kyuro SASAKI

7

SATELLITE REMOTE SENSING FOR CHARACTERIZING PROGRESS OF DESERTIFICATION IN THE NORTHERN TARIM BASIN, CHINA

Wayit AYSHAMGU and Katsuaki KOIKE

15

NUMERICAL MODELLING OF MINING-INDUCED ENERGY IN A CUT-AND-FILL MINE

Ridho Kresna WATTIMENA

21

THREE DIMENSIONAL SIMULATION OF ROCK FRACTURES BY GEOSTATISTICAL METHOD WITH CONSIDERATION OF DIRECTIONAL ELEMENTS

Chunxue LIU, Katsuaki KOIKE and Tomoji SANGA

29

ONE-DIMENSIONAL CONSOLIDATION CHARACTERISTICS OF COARSE TYPE BARRIERS

Anel A. ROBERTS and Takayuki SHIMAOKA

37

ACID ROCK DRAINAGE MANAGEMENT AND ITS RELATIONSHIP WITH WATER QUALITY REGULATIONS FOR MINING INDUSTRY IN INDONESIA

Candra NUGRAHA, Kikuo MATSUI, Hideki SHIMADA and Takashi SASAOKA

45

ANALYSIS OF THE CHARACTERISTICS OF MAGNITUDE AND PREDICTION OF PROPAGATION OF BLAST VIBRATION IN LIMESTONE QUERRY

Sugeng WAHYUDI, Hideki SHIMADA, Takashi SASAOKA, Kikuo MATSUI, Masatomo ICHINOSE, Budi SULISTIANTO, A.P.WIBOWO, Suseno KRAMADIBRATA and Ganda Marihot SIMANGUNSONG

53

SPATIO-TEMPORAL PREDICTION OF WATER INFLOW AND ITS INFLUENCE ON GROUNDWATER LEVEL DUE TO TUNNEL EXCAVATION

Chunxiang WANG, Tetsuro ESAKI, Yasuhiro MITANI and Asuka MURAKAMI

59

INTERACTION OF Co(II) IONS WITH THE BIOGENIC Mn OXIDE PRODUCED BY PARACONIOTHYRIUM SP.-LIKE STRAIN OF FUNGUS

Keiko SASAKI, Minoru MATSUDA and Tsuyoshi HIRAJIMA

67

GEOCHEMICAL CHARACTERIZATION OF ROCK SAMPLES FROM COAL MINE FOR ASSESSING THE ACID MINE DRAINAGE POTENTIAL	75
<i>Rudy Sayoga GAUTAMA, Ginting Jalu KUSUMA and Andri ABDULLAH</i>	
INNOVATIVE OPEN CAST DESIGN BY BPITC APPROACH	83
<i>Charles DINDIWE and Kyuro SASAKI</i>	
STRESS DISTRIBUTION AND DISPLACEMENT ANALYSIS IN A STOPE IN PONGKOR UNDERGROUND GOLD MINE	91
<i>M. Safrudin SULAIMAN, Budi SULISTIANTO, Ridho. K. WATTIMENA, Suseno KRAMADIBRATA, Barlian DWINAGARA, Kikuo MATSUI and Iwan Dharma SETIAWAN</i>	
RESIDENCE TIME DISTRIBUTION (RTD) IN LARGE FLOTATION CELLS AT PT FREEPORT INDONESIA	99
<i>Edy SANWANI</i>	
HISTORY MATCHING OF LONG-TERM PERFORMANCE OF A GEOHP SYSTEM IN SHIRAKAMI MOUNTAINS	109
<i>Takashi ISHIKAMI, Hikari FUJII, Mayumi KINOSHITA and Ryuichi ITOI</i>	
GEOCHEMISTRY OF ARSENIC MOBILIZATION IN GROUNDWATER, MEKONG DELTA, VIETNAM	117
<i>Nguyen Kim PHUONG, Ryuchi ITOI and Rie UNOKI</i>	
THERMAL POWER PLANTS SITE SELECTION USING GIS IN FARS PROVINCE SOUTHERN PART OF IRAN	135
<i>Hossein YOUSEFI, Sachio EHARA, Reza SAMADI, Tika SOHRAB and Younes NOOROLAHI</i>	
EVALUATION OF THE INDUSTRIAL WASTE DATA COLLECTION SYSTEM IN THAILAND	147
<i>Patsaraporn PLUBCHAROENSUK, Hirofumi NAKAYAMA and Takayuki SHIMAOKA</i>	
SYNTHESIS OF HYDROTHERMAL MINERALS FROM MUNICIPAL SOLID WASTE INCINERATORS RESIDUES	155
<i>Jiro ETOH, Takayuki SHIMAOKA and Koichiro WATANABE</i>	
PRELIMINARY STUDY HYDROTHERMAL SYSTEM OF UNGARAN VOLCANO, INDONESIA INFERRED FROM GEOPHYSICAL SURVEYS	163
<i>Agus SETYAWAN, Sachio EHARA, Yasuhiro FUJIMITSU, Jun NISHIJIMA, Koichiro FUKUOKA and WAHYUDI</i>	

DETAILED MAPPING OF SPATIO-TEMPORAL VARIABILITY OF SHALLOW GROUNDWATER LEVELS USING MULTIVARIATE COKRIGING	169
<i>Moukanà Jean AURELIEN and Katsuaki KOIKE</i>	
FAULT ZONE CHARACTERIZATION IN GEOTHERMAL FIELD BY 3D GEOLOGIC MODELING AND RADON PROSPECTING	175
<i>Yun TENG, Kenta SUETSUGU, Tohru YOSHINAGA and Katsuaki KOIKE</i>	
CLARIFICATION OF FLOW AREAS OF VOLCANIC MATERIALS ACCOMPANIED BY THE HISTORICAL ERUPTION OF MT. MERAPI, INDONESIA USING RADARSAT SAR IMAGES	181
<i>Asep SAEPULOH, Katsuaki KOIKE and Makoto OMURA</i>	
PERMEABILITY ESTIMATION IN GEOTHERMAL AREA BY INVERSION ANALYSIS OF 3D TEMPERATURE DISTRIBUTION USING WELL-LOGGING DATA	187
<i>Yun TENG and Katsuaki KOIKE</i>	
POTENTIAL OF ARTIFICIAL GROUNDWATER RECHARGE THROUGH SURFACE RESERVOIR FOR JAKARTA AQUIFER	193
<i>Lambok M. HUTASOIT, Irwan ISKANDAR and Agus M. RAMDHAN</i>	
HYDROGEOLOGICAL CHARACTERIZATION OF FRACTURE MEDIA IN GUDANG HANDAK VEIN-PONGKOR GOLD MINE PT ANEKA TAMBANG, TBK., INDONESIA	201
<i>Ginting Jalu KUSUMA and Rudy Sayoga GAUTAMA</i>	
IRON SAND CHARACTERISTICS OF SOUTH JAVA COAST, CASE STUDY OF IRON SAND MAPPING IN KULONPROGO AND BANTUL COAST, INDONESIA	211
<i>Komang ANGGAYANA, Bambang KUNCORO, Agus Haris WIDAYAT, Sudarto NOTOSISWOYO and Budi SULISTIJO</i>	
XPS STUDY ON CHARACTERIZATION OF ARSENIC IMMOBILIZED IN ABIOTIC PERMEABLE REACTIVE BARRIER (PRB) TREATMENT USING ZERO VALENCE IRON (ZVI)	219
<i>Keiko SASAKI, Hironobu NAKANO, Yoshinori MIURA and Tsuyoshi HIRAJIMA</i>	
IMMOBILIZATION OF As (III) AND As (V) IN GROUNDWATER BY PERMEABLE REACTIVE BARRIERS USING IRON GRANULAR AND COW MANURE	227
<i>Wahyu WILOPO, Keiko SASAKI and Tsuyoshi HIRAJIMA</i>	
SURFACE MODIFICATION OF QUARTZ USING SIP PRODUCING E. COLI	235
<i>Mohsen FARAHAT, Tsuyoshi HIRAJIMA, Keiko SASAKI, Yuuki AIBA, Yasuhiro FUJINO and Katsumi DOI</i>	

ALKALI HYDROTHERMAL TREATMENT OF BIOMASS	241
<i>Moriyasu NONAKA, Tsuyoshi HIRAJIMA, Junpei YABUKI and Keiko SASAKI</i>	
SLAKING BEHAVIOR OF COAL MEASURE ROCKS CATEGORIZED BY NAG TEST AT COAL MINE IN INDONESIA	247
<i>Jiro OYA, Hideki SHIMADA, Kikuo MATSUI, Masatomo ICHINOSE and Takashi SASAOKA</i>	
IMPEDANCE CHARACTERISTIC OF CHALCOCITE AND COVELLITE - XANTHATE IN FLOTATION	253
<i>Ismi HANDAYANI</i>	
THE USE OF FLYASH FOR REMOVAL OF HEXAVALENT CHROM IONS FROM AQUEOUS SOLUTION	263
<i>A. PRASETYA, C.W. PURNOMO and A. A. DWIATMOKO</i>	
MEASUREMENTS OF CH ₄ AND CO ₂ ADSORPTION ISOTHERMS FOR COALS AND ITS ROLE TO ENHANCING COAL BED METHANE AND CO ₂ SEQUESTRATION	271
<i>Phung Quoc HUY, Kyuro SASAKI and Yuichi SUGAI</i>	
A LABORATORY EXPERIMENTS FOR TRACER GAS DIFFUSION	279
<i>Nuhindro Priagung WIDODO, Kyuro SASAKI, Yuichi SUGAI, R.S. GAUTAMA and A. WIDIATMOJO</i>	
RECOVERY OF PHOSPHOROUS FROM SEWAGE SLUDGE AS MAP AND ITS UPGRADING BY MAGNETIC SEPARATION	285
<i>Tsuyoshi HIRAJIMA, Mia KOSE, Keiko SASAKI and Takao HAGINO</i>	
DESIGN OF SPATIAL DECISION SUPPORT SYSTEM FOR DETECTING THE SIGNS OF VOLCANO HAZARDS	291
<i>Silmi FAUZIATI, Lucas Donny SETIJADJI and Koichiro WATANABE</i>	
GEOCHEMICAL CHARACTERIZATION OF THE INTRUSIVE ROCKS AT THE KINGKING PORPHYRY COPPER-GOLD DEPOSIT, EASTERN MINDANAO, PHILIPPINES	299
<i>Leilanie O. SUERTE, Sho NISHIHARA, Akira IMAI, Koichiro WATANABE, Graciano P. YUMUL, Jr. and Vict B. MAGLAMBAYAN</i>	
STUDY ON ADSORPTION OF AU(I) AND AU(III) ANIONS ONTO MANGANESE DIOXIDE FOR APPLICATION TO THEIR RECOVERY FROM GEOTHERMAL WATER	307
<i>Sachihiro SAKOMOTO, Kotaro YONEZU, Takushi YOKOYAMA, Yoshihiro OKAUE, Akira IMAI and Koichiro WATANABE</i>	
UNDERGROUND MINING IN PAPUA NEW GUINEA	313
<i>Gabriel ARPA and Khanindra PATHAK</i>	

GRAVITY STUDY OF JATIBARANG SUB-BASIN AND SURROUNDING AREA; IMPLICATION TO HEAT FLOW MAP OF ON SHORE NORTH WEST JAVA BASIN, INDONESIA	321
<i>SURYANTINI , Jun NISHIJIMA, Sachio EHARA and Aris SUSILO</i>	
VARIATIONS IN GEOTHERMOMETRY AND CHEMICAL COMPOSITION OF HOT SPRING FLUIDS IN THE OBAMA GEOTHERMAL FIELD, SOUTHWESTERN JAPAN	329
<i>Hakim SAIBI, Sachio EHARA, Yasuhiro FUJIMITSU and Jun NISHIJIMA</i>	
STUDY OF POLLUTANT DISCHARGE ESTIMATION UNDER PARAMETER UNCERTAINTIES	341
<i>Budi KURNIAWAN and Kenji JINNO</i>	
DENITRIFICATION OF SECONDARY WASTEWATER USING SAWDUST	349
<i>Osama MM ELJAMAL, Kenji JINNO and Tosao HOSOKAWA</i>	
GAS PRODUCTION FROM METHANE HYDRATE DEPOSITS BY THERMAL STIMULATION USING GEOTHERMAL HEAT SOURCE AND DEPRESSURIZATION	357
<i>Hikari FUJII, Yusuke WASAKI and Ryuichi ITOI</i>	
GEOLOGICAL AND GEOCHEMICAL STUDY ON THE UNGARAN GEOTHERMAL FIELD, CENTRAL JAVA, INDONESIA: AN IMPLICATION IN GENESIS AND NATURE OF GEOTHERMAL WATER AND HEAT SOURCE	367
<i>Yasuaki KOHNO, Sachihito TAGUCHI, Harijoko AGUNG, Utami Pri, Akira IMAI and Koichiro WATANABE</i>	
RESERVOIR MANAGEMENT FOR SUSTAINING INJECTIVITY AND PRODUCTIVITY OF WELLS IN THE HATCHOBARU GEOTHERMAL FIELD	375
<i>Tetsuya YAHARA, Hiroki SAITO, Ryuichi ITOI and Nobuyuki TAKESHIMA</i>	
RELATIONSHIP BETWEEN EXCESS PORE PRESSURE, PERMEABILITY AND HEAT FLOW DISTRIBUTION AT THE TOE OF THE NANKAI TROUGH	383
<i>Keiko FUJINO, Masataka KINOSHITA and Sachio EHARA</i>	
NUMERICAL STUDY OF PRESSURE CHANGE IN A CRYSTALLIZING, VOLATILE-SATURATED MAGMA RESERVOIR CAUSING ERUPTION	391
<i>Mitsuo MATSUMOTO and Sachio EHARA</i>	
POTENTIAL OF ANDISOL AROUND MT. ISAROG IN THE PHILIPPINES FOR THE REMOVAL OF Cr (VI) FROM AQUEOUS SYSTEMS	399
<i>Einstine M. OPISO and Sandhya BABEL</i>	

REGIONAL AND LOCAL SCALE GEOTHERMAL RESOURCES EXPLORATION AND POTENTIAL SITE SELECTION USING GIS IN ARDEBIL PROVINCE NORTHWESTERN IRAN	407
<i>Younes NOOROLLAHI, Ryuichi ITOI, Hikari FUJII and Toshiaki TANAKA</i>	
MINERALOGICAL CHARACTERISTICS OF THE SAMPANG ZEOLITIC TUFF, GUNUNGKIDUL – INDONESIA AND ITS UTILIZATION AS FERTILIZER	423
<i>Anastasia Dewi TITISARI, Arifudin IDRUS and WIDIASMORO</i>	
OCCURRENCE AND DISTRIBUTION OF GOLD IN PRECIPITATES FROM THE WELLHEAD STEAM SEPARATOR AT OTAKE GEOTHERMAL POWER PLANT	431
<i>Kotaro YONEZU, Shu HAYASHI, Takushi YOKOYAMA, Yoshinobu MOTOMURA, Akira IMAI and Koichiro WATANABE</i>	
COMPOSITIONAL VARIATIONS OF PROPYLITIC-RELATED DIAGNOSTIC MINERALS AT THE BATU HIJAU PORPHYRY COPPER-GOLD DEPOSIT, INDONESIA: AN IMPLICATION FOR HYDROTHERMAL FLUID CHEMISTRY	439
<i>Arifudin IDRUS, Jochen KOLB and Franz Michael MEYER</i>	
CASE STUDY OF SELECTIVE MINING AND HOMOGENISATION	449
<i>Alois BURÝ</i>	
VISUALIZATION AND PROCESSING OF DATA PROVIDED BY MINING SYSTEMS	455
<i>Robert KLIMUNDA and Richard ŠIMEK</i>	
SIMULINK COMPUTER PROGRAM APPLICATION FOR SELECTIVE MINING PURPOSES	461
<i>Miloš JENDRYŠČÍK and Alois BURÝ</i>	
THE PROBLEMS OF COAL AND GASES IN THE CZECH REPUBLIC IN THE PASKOV MINE	467
<i>Vlastimil HUDEČEK and Petr MICHALČÍK</i>	
MATHEMATICAL MODELS OF THE FLOWING OF THE MINE ATMOSPHERE UPRISING OUT OF THE DEGASIFYING HOLE	475
<i>Jan PRAVŇANSKÝ</i>	
SIMULATION OF INFLUENCE INDUSTRIAL PRODUCTION WITH REGARD ON POPULATION'S FACTORS	481
<i>Richard ŠIMEK</i>	
TRAINING PROCESSES OF ARTIFICIAL MULTILAYER NEURAL NETWORKS	487
<i>Michal ŘEPKA</i>	

THE ENVIRONMENTAL BURDEN OF HAZARDOUS ELEMENTS IN ANTHROPOSOLS OF SPOIL BANKS OF THE NORTH BOHEMIAN BROWN COAL BASIN	495
<i>Petr ČERMÁK, Hana LORENCOVÁ and Michal ŘEHOŘ</i>	
NEWS WORKING INFORMATIONS ON GASSY MINES	499
<i>Vladislav VANČURA and Lukáš OTTE</i>	
THE FIELD TEST OF THE GROUND MOVEMENTS BY THE EXPANDIT PIPE BURSTING AND REPLACEMENT SYSTEM	505
<i>Reizo YAMAOKA, Masaya HIRAI, Hideki SHIMADA, Takashi SASAOKA and Kikuo MATSUI</i>	
CHARACTERIZATION OF BAMBOO UPGRADED BY HYDROTHERMAL TREATMENT	517
<i>Tsuyoshi HIRAJIMA, Jumpei YABUKI, Moriyasu NONAKA and Keiko SASAKI</i>	
DIGITAL VOLCANO: AN EXPERIMENTAL DESIGN OF SPATIAL DATABASE FOR A VOLCANO AND ASSOCIATED PHENOMENA	523
<i>Lucas Donny SETIJADJI, Yasuaki KOHNO, Akira IMAI and Koichiro WATANABE</i>	
RELATIONSHIPS BETWEEN EARTHQUAKE AND VOLCANIC ACTIVITY: THE CASE OF MERAPI VOLCANO AND THE 27 MAY 2006 EARTHQUAKES IN YOGYAKARTA REGION, INDONESIA	533
<i>Lucas Donny SETIJADJI and Koichiro WATANABE</i>	
THE KONKOLA DEEP MINING PROJECT IN ZAMBIA	541
<i>Stephens M. KAMBANI</i>	
THE APPLICATION OF SAMPLE DISPLACEMENT MONITORING SYSTEM FOR ROCK/SOIL MOVEMENT AT BINUNGAN MINE OPERATION, OF PT. BERAU COAL	549
<i>ZULFAHMI and Eko PUJIANTO</i>	
STUDY OF GASES FROM PT.BUKIT ASAM COAL MINE, TANJUNG ENIM, SOUTH SUMATRA	559
<i>Asnawir NASUTION, Lambok HUTSOIT and Sofyan PRAMULYANA</i>	

STRESS DISTRIBUTION AND DISPLACEMENT ANALYSIS IN A STOPE IN PONGKOR UNDERGROUND GOLD MINE

M. Safrudin SULAIMAN¹, Budi SULISTIANTO¹, Ridho. K. WATTIMENA¹, Suseno KRAMADIBRATA¹,
Barlian DWINAGARA¹, Kikuo MATSUI² and Iwan Dharma SETIAWAN³

¹Department of Mining Engineering, Institute of Technology Bandung, Bandung 40132, Indonesia

²Kyushu University, Fukuoka 819-0395, Japan

³Gold Mining Business Unit of Pongkor, PT. ANTAM, Tbk., Indonesia

E-mail : safrudin@mining.itb.ac.id

ABSTRACT

Pongkor is one of the underground gold mines in Indonesia which applies the cut-and-fill mining method. During the mining, the stability of mine opening is one of the factors deciding the continuity of underground mining process. Due to the mining activity, stresses around the mining area will be redistributed, and in some condition they may lead to a failure on the stope. To avoid such failure, it is important to monitor the deformation and understand the stress redistribution effects on surrounding rock mass as the mining activity proceeded. A borehole extensometer was installed in the ore body to monitor the rock mass displacement, and a 3D model of the mining sequence was made to understand the stress redistribution in the surrounding rock mass.

INTRODUCTION

Pongkor underground gold mine carries out a cut-and-fill mining method to excavate the vein ore body. The stope mining activity is carried out in slice which is 100m in length, 3m in height and the width follows the potential ore body. In some occasion, failures happen around the stope opening, mostly in the stope roof, which may affect the mining activity. To avoid such condition, analysis is carried out to understand the influence stress distribution due to stope mining activity of the surrounding rock mass through a monitoring station located above the stope.

The aim of this study is to analyze the stress redistribution and rock deformation in the roof due to stoping activity. Deformation analysis was carried out by drilling a set of borehole in a crosscut located above the stope and the stress redistribution in surrounding rock mass is analyzed by using a 3D model regarding the mining location and mining sequence. This research is a continuation of the previous study carried out by Dwinagara, et.al., 2006.

NUMERICAL MODELLING

Numerical modeling was carried out to understand the stress redistribution due to mining activities located below the monitoring station. The model was also used to verify the direct measurement (horizontal extensometer). FLAC3D program was used to analyze the stress redistribution by assuming the rock mass as continuous material. The model represented the location of monitoring station in crosscut 6A in Level 500 of Block II Central Ciurug, at an elevation of 568 m, around 300 m from the surface (Dwinagara, et.al., 2006). The stope was located below monitoring station, and the vertical distance between the floor of crosscut 6A and the stope roof was about 3 m. As can be seen in Figure 1, the stoping was started from the stope 1 (located at bottom part) and move upward to

higher stope number (stope 10). The length of each stope excavation was about to 10m. Due to the stope mining process, stresses in rock mass around the monitoring station were affected.

The inputs for the numerical model were stope geometry, mining sequences, rock mass properties, and in situ stresses at the location. The stope was approximately 5 m wide and the thickness of mining slice was 3 m. Rock mass properties were taken from the laboratory test (See Table 1). The in situ stresses used as the input in this model were obtained from previous research located near to this location (Sulistanto, et.al., 2003) (See Table 2).




Figure 1. Numerical Model of the Location and Stope Mining Direction

Table 1. Rock Properties

Rock Type	γ (kN/m^3)	E (GPa)	ν
Andesitic Breccia (FW & HW)	27.3	12.35	0.26
Vein	26.9	5.25	0.26

Table 2. Insitu Stresses

Stress	Magnitude	
σ_x	0.61	MPa
σ_y	3.62	MPa
σ_z	3.88	MPa
σ_{xy}	0.73	MPa
σ_{yz}	0.79	MPa
σ_{xz}	-0.83	MPa

DISPLACEMENT MEASUREMENT

The displacement measurement was carried out from the monitoring station at crosscut 6A, by using *Intrinsically Safe Magnesonic Probe Extensometer* of Type 1062. Two boreholes which oriented horizontally and vertically were drilled into the vein to install the extensometer magnetic anchors ($T_0 - T_4$), as illustrated in Figure 2. Since this analysis was focused on the stability of the stope's roof, only the horizontal extensometer displacements were taken into account.

The displacement calculation was based on the change of distance between the two magnetic anchors as follows:

$$\Delta L = L_t - L_0 \quad (1)$$

Where: ΔL = distance change (displacement), mm

L_t = final distance at time t, mm

L_0 = initial distance, mm

The initial positions of the horizontal magnetic anchors are listed in Table 3. At the beginning of the measurement, the stope was approximately 45 m (horizontal) from the station. The mining then moved towards the station (distance of 0 m) and then passed the station.




Figure 2. Magnetic Anchors Placement in Borehole (Dwinagara, et.al., 2006)

Table 3. Initial Positions of Horizontal Magnetic Anchors from Collars

Anchor	Front Borehole	
	Position	Rock
T ₁	1146 mm	Vein
T ₂	2365 mm	Vein
T ₃	3867 mm	Vein
T ₄	5887 mm	Hanging wall

Graphs depicting the accumulative displacements of front borehole as the stoping move forward to the station and passed the station are given in Figure 3.





Figure 3. Accumulative Displacement along Horizontal Borehole Extensometer (Dwinagara, et.al., 2006)


STRESS AND DEFORMATION RESULT FROM NUMERICAL MODELING

Stress distribution change was monitored in some points. The location points which were analyzed in the numerical model were the same as the horizontal extensometer monitoring points. As the horizontal points were located in the both edges and in the middle of the ore body, they may be considered representing the behaviour of the ore body in the horizontal direction.

Due to stope mining activities located beneath the monitoring station, the monitoring points located in the ore body would suffer stress redistribution. The analysis was also conducted on the rock mass deformation in the same points. The result of the stress change and deformation from numerical model are shown in Figure 4 to Figure 6.




(a) Stress change




(b) Deformation change

Figure 4. Stress and Deformation Change in X Axis Direction




(a) Stress change




(b) Deformation change

Figure 5. Stress and Deformation Change in Y Axis Direction



(a) Stress change



(b) Deformation change

Figure 6. Stress and Deformation Change in Z Axis Direction

DISCUSSION

Stoping induced stress

The stoping which is moving forward to the monitoring station and located beneath will affect the stress distribution around this location. The data obtained from numerical model shows that the points which were monitored also suffer stress redistribution.

Figures 4 to 6 show that the effect of stoping to stress redistribution started when the stope 4 was excavated. The horizontal distance of stope face to the monitoring station is about 20m. The stresses change significantly when stopes 5 and 6 were excavated. The location of those stopes which are on the lower right from the monitoring station, was the cause of the significant stress change. When the stopes were excavated an opening was formed right below the monitoring station causing major stress redistribution around the location. The stresses tended to be relatively constant after the excavation of stope 7 which horizontal distance of stope mining was about 20m.

Displacement Comparison between Extensometer Measurement and Numerical Modelling

By using the deformation data obtained from the numerical modelling (Figure 4-6), the movement of the monitoring points could be well understood. From those figures, it can be found that the stope started to influence the monitoring point after stope 4 was excavated. Figure 4 shows that the deformations in the x-direction show a tendency that the points became closer to each other. T1 and T2 moved forward (positive x-direction) while and T3 and T4 moves backward (negative x-direction). The deformation ranged from 0.1m to 0.25mm.

Figure 5 shows that the y-direction deformation of the rock mass had a tendency to move toward to location where mine opening exists. As can be seen that before the excavating of stope 5, the points moved to the right (negative y-direction) and after passing stope 5, the points moved to left (positive y direction). The displacement ranged from -0.28mm to 0.14mm. The z-direction displacement show that all points moved downward. As the point located farther from footwall, the displacement value will be higher. The z deformation value ranges from 0.7mm to 1.5mm.

Since the data obtained from borehole extensometer measurement is only in x-axis, the best way to compare to the numerical data was do the analysis in 2 dimension (x axis and z axis). The coordinate of monitoring points before and after stope excavation are given in Table 4, while the distances between monitoring anchors are given in Table 5.

Table 4. Monitoring Points Coordinate in Numerical Model

Points	Before stope excavation		After stope excavation	
	X	Z	ΔX	ΔZ
T1	30.147	22	4.3E ⁻⁰⁴	-2.3E ⁻⁰³
T2	31.365	22	2.1E ⁻⁰⁴	-3.8E ⁻⁰³
T3	32.867	22	-2.5E ⁻⁰⁴	-4.8E ⁻⁰³
T4	32.887	22	-8.3E ⁻⁰⁴	-4.9E ⁻⁰³

Table 5. Distance Change of Monitoring Points from Numerical Model

Points	Distance (m)		
	Before stope excavation	After stope excavation	Delta
T4-3	2.02	2.019421499	-1.26E ⁻⁰³
T4-2	3.522	3.520954588	-1.05E ⁻⁰³
T4-1	4.74	4.738742431	-5.79E ⁻⁰⁴


The distance change of monitoring points from numerical model revealed that there was a shortening along horizontal borehole extensometer and different from direct measurement result (Figure 3) which showed an extension. It may happen due to the existence of geological structures which developed around the location and which was not included in the numerical model.

STABILITY OF STOPE'S ROOF DUE TO MINING ACTIVITY

One of the factors which may lead to underground instability is the induced stress around the opening. The mining activity it self can change the condition of insitu stress. During the stope mining activity, the maximum stress (σ_1) and minimum stress (σ_3) in the monitoring points suffer changes. In this work, the monitoring points were located in the rock mass which acts as stope's roof. As can be seen in Figure 7, the maximum stress started to increase when stope 5 was excavated due to stress redistribution. Since there was an opening near the monitoring station, the stress was transferred to neighbouring rock mass, which one of monitoring stations (horizontal extensometer) was located.

The maximum stress in T1 increased while stresses in other points relatively decreased. This condition was due to the geometry of the opening which may cause the stress to concentrate at some of the edges of the opening, while in other edges the stress was redistributed.

Figure 7 also shows that the minimum stress in all monitoring points decrease. At the edge of the opening which is represented by T1, the combination of increasing maximum stress and decreasing minimum stress means that the loading condition is increasing. As the loading condition increases and the rock mass strength is constant the safety factor value for the underground opening will be decrease.



(a) Maximum stress (σ_1) change

(b) Minimum stress (σ_3) change

Figure 7. Maximum and Minimum Stress changes

CONCLUSION

From the analysis above, it can be seen that the stress started to affect the monitoring points and leave the steady condition when the horizontal distance from the stope face was approximately 20m. The extension of horizontal borehole extensometer from direct measurement was caused by the existence of geological structure rather than the stress redistribution, as the continuous numerical model shows the opposite result.

The stress redistribution in the stope roof caused by stoping activity with its specific opening geometry, caused a stress concentration the edge of the opening. The stress redistribution may cause the increasing of rock mass loading condition and decrease the safety factor of the opening.

ACKNOWLEDGEMENTS

The authors thank the Pongkor Gold Mining Business Unit of PT. Antam, Tbk. for all supports for this tripartite research and Mr Ronald Sibarani for giving permission to use the FLAC3D program.

REFERENCES

- Sulistianto, B., Rai, M.A., Kramadibrata, S., Hartami, P.N., Matsui, K., Nakagawa, H., Setiawan, I.D., Janu, E. & Risono, 2003b, *Determination of insitu stress using hydraulic fracturing method at Pongkor underground gold mine, West Java, Indonesia*; Proceedings of The Third International Symposium on Rock Stress, RS Kumamoto, 4-6 November 2003, Kumamoto, Japan, Edited by Sugawara, K., Obara, Y., Sato, A : 383-388., AA. Balkema Publishers, Tokyo (2003).
- Dwinagara, B., Sulistianto, B., Wattimena, R.K., Kramadibrata, S., Sulaiman, M.S, Matsui, K., Setiawan, I.D, 2005, *Stoping-induced Displacements in a Fractured Vein at Pongkor Underground Gold Mine, Indonesia*, Proceedings of International Workshop on Earth Science and Technology, Fukuoka, Japan, November (2005).
- “*FLAC3D Ver 2.0 User's Manual*”, Itasca Consulting Group, Minneapolis, Minnesota 55415 USA (1997).