

DAFTAR ISI

LEMBAR PENGESAHAN	iii
PERNYATAAN KEASLIAN KARYA ILMIAH	iv
HALAMAN PERSEMBAHAN	v
PRAKATA	vi
RINGKASAN	viii
ABSTRACT	ix
DAFTAR ISI	x
DAFTAR GAMBAR	xii
DAFTAR TABEL	xiii
DAFTAR LAMPIRAN	xiv
DAFTAR SINGKATAN DAN LAMBANG	xv
BAB I PENDAHULUAN	1
I.1 Latar Belakang	1
I.2 Maksud dan Tujuan	2
I.3 Batasan Masalah	2
I.4 Metodologi	3
I.5 Sistematika Penulisan	5
BAB II TINJAUAN LAPANGAN	6
II.1 Lokasi Geografis	6
II.2 Struktur Geologi	7
II.3 Stratigrafi Regional Cekungan Sumatera Tengah	7
II.4 <i>Petroleum System</i> Cekungan Sumatera Tengah	11
BAB III DASAR TEORI	12
III.1 Fungsi <i>Casing</i>	12
III.2 Klasifikasi <i>Casing</i>	13
III.2.1 <i>Conductor Casing</i>	14
III.2.2 <i>Surface Casing</i>	14
III.2.3 <i>Intermediate Casing</i>	15
III.2.4 <i>Production Casing</i>	15

III.2.5	<i>Liner</i>	15
III.3	Spesifikasi dan Kekuatan <i>Casing</i>	15
III.3.1	Diameter	15
III.3.2	Berat <i>Casing</i>	16
III.3.3	<i>Grade Casing</i>	17
III.3.4	<i>Joint Length Casing</i>	18
III.3.5	Tipe Sambungan <i>Casing</i>	18
III.3.6	<i>Internal Yield Pressure</i>	20
III.3.7	<i>Maximum Collapse Resistance</i>	20
III.3.8	<i>Safety Factor</i>	20
III.4	Gaya dan Tekanan <i>Casing</i>	22
III.4.1	<i>Internal Pressure (Burst)</i>	23
III.4.2	<i>External Pressure (Collapse)</i>	25
III.4.3	<i>Tension Load</i>	26
III.4.4	<i>Biaxial</i>	28
III.5	Faktor yang Mempengaruhi Desain <i>Casing</i>	31
III.6	Metode <i>Maximum Load</i>	36
III.7	<i>Software Stresscheck</i>	36
III.8	Biaya Desain <i>Casing</i>	37
BAB IV PERHITUNGAN PEMILIHAN <i>GRADE CASING</i> PADA SUMUR “RR-20” LAPANGAN “SPC”		39
IV.1	Data Sumur “RR-20”	39
IV.2	Desain <i>Casing</i> “RR-20”	41
IV.2.1	Perhitungan <i>Burst Load</i>	41
IV.2.2	Perhitungan <i>Collapse Load</i>	43
IV.2.3	Perhitungan <i>Tension Load</i>	46
IV.3	Pemilihan <i>Grade Casing</i> Sumur “RR-20”	48
IV.3.1	Evaluasi Beban <i>Casing</i> Manual	48
IV.3.2	Evaluasi Beban <i>Casing</i> Menggunakan <i>Software Stresscheck</i>	53
IV.3.3	Perhitungan Biaya <i>Casing</i>	58
BAB V PEMBAHASAN		59
BAB VI KESIMPULAN		64
DAFTAR RUJUKAN		65
LAMPIRAN		66

DAFTAR GAMBAR

Gambar I.1	<i>Flowchart</i> Penelitian	4
Gambar II.1	Peta Lokasi Lapangan "SPC"	6
Gambar II.2	Stratigrafi Cekungan Sumatera Tengah	10
Gambar III.1	Klasifikasi <i>Casing</i>	14
Gambar III.2	Tipe Sambungan <i>Casing</i>	18
Gambar III.3	<i>Round Thread Coupling</i> (RTC)	19
Gambar III.4	<i>Buttress Thread Coupling</i> (BTC)	19
Gambar III.5	<i>Extreme-Line Thread Coupling</i>	20
Gambar III.6	<i>Internal Pressure</i>	23
Gambar III.7	<i>External Pressure</i>	25
Gambar III.8	Analisa <i>Biaxial Stress</i>	28
Gambar III.9	<i>Biaxial Stress</i>	29
Gambar III.10	<i>Triaxial Stress</i>	31
Gambar III.11	Pemilihan Ukuran <i>Bit</i> dan <i>Casing</i>	35
Gambar III.12	Contoh <i>Design Limit</i> Hasil <i>Software Stresscheck</i>	37
Gambar IV.1	Perbandingan Hasil <i>Burst Surface Casing</i> 9 5/8" sumur "RR-20"	50
Gambar IV.2	Perbandingan Hasil <i>Collapse Casing Surface</i> 9 5/8" sumur "RR-20"	50
Gambar IV.3	Perbandingan Hasil <i>Burst Production Casing</i> 7" sumur "RR-20"	51
Gambar IV.4	Perbandingan Hasil <i>Collapse Casing Production</i> 7" sumur "RR-20"	52
Gambar IV.5	Keterangan Gambar Parameter pada <i>Design Limit</i>	53
Gambar IV.6	Hasil Beban <i>Burst</i> , <i>Collapse</i> , <i>Tension</i> , dan <i>Triaxial</i> untuk <i>casing grade</i> K-55 36 ppf	54
Gambar IV.7	Hasil Beban <i>Burst</i> , <i>Collapse</i> , <i>Tension</i> , dan <i>Triaxial</i> untuk <i>casing grade</i> H-40 32,3 ppf	54
Gambar IV.8	<i>Design Limit</i> untuk <i>casing grade</i> K-55 36 ppf	55
Gambar IV.9	<i>Design Limit</i> untuk <i>casing grade</i> H-40 32,3 ppf	55
Gambar IV.10	Hasil Beban <i>Burst</i> , <i>Collapse</i> , <i>Tension</i> , dan <i>Triaxial</i> untuk <i>casing grade</i> K-55 26 ppf	56

Gambar IV.11	Hasil Beban <i>Burst</i> , <i>Collapse</i> , <i>Tension</i> , dan <i>Triaxial</i> untuk casing grade K-55 23 ppf	56
Gambar IV.12	<i>Design Limit</i> untuk casing grade K-55 26 ppf	57
Gambar IV.13	<i>Design Limit</i> untuk casing grade K-55 23 ppf	57

DAFTAR TABEL

Tabel III-1	<i>API Manufacturing Tolerance Outside Diameter</i>	16
Tabel III-2	<i>API Manufacturing Tolerance Drift Diameter</i>	16
Tabel III-3	Klasifikasi <i>Casing Grade</i> standar API	17
Tabel III-4	Standart API Panjang <i>Joint Casing</i>	18
Tabel III-5	<i>Safety Factor</i> standar <i>Pertamina Drilling Way</i>	21
Tabel III-6	Pasangan Nilai X dan Y <i>Collapse Rating</i>	30
Tabel IV-1	Profil Sumur “RR-20”	39
Tabel IV-2	Data <i>Surface Casing</i>	39
Tabel IV-3	Data <i>Production Casing</i>	40
Tabel IV-4	<i>Safety Factor</i> Standar <i>Pertamina Drilling Way</i>	40
Tabel IV-5	Program Desain <i>Casing</i> Sebelumnya	48
Tabel IV-6	Program Desain <i>Casing</i> Setelah Evaluasi dan Optimasi	49
Tabel IV-7	Hasil <i>Safety Factor</i> Desain <i>Casing</i> Sebelumnya	52
Tabel IV-8	Hasil <i>Safety Factor</i> Setelah Optimasi Desain <i>Casing</i>	52
Tabel IV-9	Biaya <i>Casing</i> Sumur RR-20 Sebelumnya	58
Tabel IV-10	Biaya Setelah Optimasi <i>Grade Casing</i> pada Sumur RR-20	58

DAFTAR LAMPIRAN

Lampiran A	Lokasi Sumur RR-20 Lapngan SPC	67
Lampiran B	Data Sumur RR-20 Lapngan SPC	67
Lampiran C	Hasil Perhitungan	71
Lampiran D	Hasil <i>Software Stresscheck</i>	72
Lampiran E	Spesifikasi <i>Casing</i>	74

DAFTAR SINGKATAN DAN LAMBANG

SINGKATAN

BOP	Blow Out Preventer
GRF	Gradien Rekah Formasi
BPD	Burst Pressure Design
CPD	Collapse Pressure Design
MW	Mud Weigh
CSD	Casing Setting Depth
IP	Injection Pressure
OD	Outside Diameter
ID	Inside Diameter
BF	Bouyancy Factor
NW	Nominal Weight
CRC	Collapse Resistance Correction
BRC	Burst Resistance Correction
MCR	Maximum Collapse Resistance
IYP	Internal Yield Pressure
API	American Petroleum Institute
SF	Safety Factor
RTC	Round Thread Coupling
BTC	Buttress Thread Coupling
ELC	Extreme Line Casing
LTC	Long Thread Coupling
KOP	Kick Of Point
EOB	End Of Build
TD	True Depth

LAMBANG

ρ_m	Densitas lumpur, ppg
D	Kedalaman, ft
Ph	Tekanan hidrostatik, psi
Ni	Safety factor Burst
Nc	Safety Factor Collapse
Nj	Safety Factor Tension
X	Faktor beban axial
Y	Faktor collapse/burst strength
Φ	Perubahan sudut (derajat/100 ft)