

## DAFTAR PUSTAKA

- Arifin, M., & Saputra, R. (2019). Pengaruh jenis material stemming terhadap kualitas fragmentasi hasil peledakan di tambang batu andesit. *Jurnal Teknologi Pertambangan*, 5(2), 77-84.
- Chen, Q., Liu, S., & Wang, X. (2023). Numerical simulation of gas flow and energy distribution in blast holes with different stemming materials. *Engineering Fracture Mechanics*, 280, 109000.
- Cunningham, C. V. B. (2005). The Kuz-Ram fragmentation model - 20 years on. In R. Holmberg, et al. (Eds.), *Proceedings of the Brighton Conference 2005* (pp. 201-210). European Federation of Explosives Engineers.
- Fitrya, M. & Yulhendra, D. (2021). Evaluasi pengaruh penggunaan jenis material dan ukuran kedalaman stemming dalam kegiatan peledakan terhadap hasil fragmentasi, cost dan recovery blasting di PT Koto Alam Sejahtera. *Bina Tambang*.
- Hakim, A., Syarif, M., & Rudianto, A. (2016). Analisis perbandingan hasil peledakan menggunakan batu pecah dan drill cutting sebagai stemming material. *Jurnal Rekayasa Tambang*, 4(2), 88-96.
- Koesnaryo. (2001). *Teknik Peledakan dalam Kegiatan Penambangan Terbuka*. Bandung: Penerbit ITB Press.
- Konya, C. J., & Walter, E. J. (1990). *Surface Blast Design*. Englewood Cliffs, NJ: Prentice-Hall.
- Kuznetsov, V. M. (1973). The mean diameter of the fragments formed by blasting rock. *Soviet Mining Science*, 9(2), 144-148.
- Lilly, P. A. (1986). An empirical method of assessing rock mass blastability. In *Proceedings of the Large Open Pit Mining Conference* (pp. 89-92). Melbourne, Australia.
- Patel, R., & Yadav, R. K. (2022). Effect of stemming compaction and particle distribution on blasting efficiency in surface mining. *Journal of Mining and Environment*, 13(3), 589-602.
- Prasetyo, D., & Putra, A. (2020). Analisis efektivitas penggunaan drill cutting sebagai material stemming pada kegiatan peledakan. *Jurnal Bina Tambang*, 6(1), 41-50.
- Rădeanu, M., Andrei, M., & Voicu, F. (2024). Energy loss mechanisms due to improper stemming conditions in open-pit blasting. *Mining Reports*, 59(1), 45-56.
- Rahmawati, S., & Yulian, D. (2020). Pengaruh ukuran dan homogenitas material stemming terhadap efisiensi konfinemen energi peledakan. *Jurnal Teknologi Mineral*, 8(1), 22-30.

- Rai, P., & Singh, T. N. (2018). Influence of rock properties and blast design parameters on fragmentation in open-pit mining. *International Journal of Rock Mechanics and Mining Sciences*, 110, 234-244.
- Rossin, P., & Rammler, E. (1933). The laws governing the fineness of powdered coal. *Journal of the Institute of Fuel*, 7, 29-36.
- Roy, S., & Singh, P. K. (2016). Effect of stemming length to hole diameter ratio on blast performance. *Journal of the Geological Society of India*, 88(4), 481-488.
- Xu, H., Li, B., & Zhang, J. (2023). Experimental study on the influence of stemming length and material on blasting performance in small-scale models. *Mining Science and Technology*, 33(2), 115-128.